



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/2852/162/12/23/2180

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :


Manufacturer : **SOCIEDAD COMERCIAL DE MARKETING M&V SPA**
Av. Amercio Vespucio 1385, Bodega 34-35, Quilicura, Santiago
CHILE

Description

PPE Type : *protective glove against mechanical risks*
Product reference : **RESISTOR FLEX55**
Article code : **EDO558 EDO559 EDO560**
Glove description : **13gauge polyester Nitrile palm coated work gloves**
Available sizes : **EDO558 (7) EDO559 (8) EDO560(9)**
Pictures :



**RESISTOR
FLEX 55**



ADD: Av. Amercio Vespucio 1385, Bodega 34-35, Quilicura, Santiago, Chile

Reference standard : **Levels of performance / class of protection**

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020	-
EN 388:2016 + A1:2018	3 1 3 2 X

At the date of the certificate, the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)
Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the user instructions index 01 dated from DECEMBER 2023.
NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
Séverine AUBERT
Certification team leader



Date of first issue : 26 December 2023
Date of end of validity : 26 December 2028



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

SOCIEDAD COMERCIAL DE MARKETING M&V SPA

MANUFACTURER'S TECHNICAL FILE TO THE
PPE REGULATION 2016/425

Reference of the product	:	RESISTOR FLEX55
Article code	:	EDO558 EDO559 EDO560
Technical file index	:	01
Last update	:	DECEMBER 2023

IDENTIFICATION

Reference of the product :	:	RESISTOR FLEX55
Article code :	:	EDO558 EDO559 EDO560
Basic Model		
Technical file index :	:	01
Last update :	:	DECEMBER 2023

Manufacturer :

SOCIEDAD COMERCIAL DE MARKETING M&V SPA
Av. Americo Vespucio 1385, Bodega 34-35, Quilicura, Santiago
CHILE

tel : 56 22 623 381

fax : 56 22 623 381

GLOVE DESCRIPTION

General glove description and intended use:

13gauge polyester Nitrile palm coated work gloves
 This glove is designed against mechanical risks.
 Type of coating finish : smooth

Visual description (picture back and palm sides) :



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.5	PPE which may be caught up during use	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	Gauges	Thickness
Palm		Black	Nitrile			0.2-0.3mm
		Red	polyester	190g/m ²	13Gauges	
Back		Red	polyester	190g/m ²	13Gauges	
Cuff		Red	polyester+elastic	300g/m ²	13Gauges	
Binding		Red	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.
This glove is designed against mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity : 5

Available size range: EDO558 (7) EDO559 (8) EDO560(9)

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388:2016 + A1:2018

Protection offered	Performance levels
Abrasion resistance	3
Blade cut resistance	1
Tear strength resistance	3
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	X
Impact Protection	N/A

The levels of performance have been measured on the palm.


TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S230605006_1 S221007039_2 (Dmfu) S230302342_1	
EN 388	S230605006_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : RESISTOR FLEX55

Article Code : EDO558 EDO559 EDO560

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :



Method of marking on the glove :

Printing on back of gloves

Packaging suitable for transport:

12 pairs per one polybag; 120 pairs per one carton.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

1:the factory director is responsible for the quality of products

2:the purchase department checks the quality of materials strictly ,every batch of materials must be fully qualified before production

3:during the production process ,our workers are divided into several teams,every team leader checks the quality in his team every one hour ,meanwhile ,the workshop manager inspects the product line randomly.Then we will send them to CTC to test abrasion test (based on EN388 standard) ,EN ISO 21420 every month....

4:the whole production process is compliance with the law of envirmetal protection and other relevant laws

5:the packagers are reaponsible to make sure thej quantity is sufficent ,before delivery ,the quality control department must do the spot check and make sure all the products are qualified

INSTRUCTIONS FOR USE

SOCIEDAD COMERCIAL DE MARKETING M&V SPA

Av. Americo Vespucio 1385, Bodega 34-35, Quilicura, Santiago
CHILE


Glove reference : RESISTOR FLEX55

Article code: EDO558 EDO559 EDO560

User notice index : 01

Last update : DECEMBER 2023

RESISTOR FLEX 55



ADD: Av. Americo Vespucio 1385, Bodega 34-35, Quilicura,
Santiago, Chile

Glove description :

13gauge polyester Nitrile palm coated work gloves

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: EDO558 (7) EDO559 (8) EDO560(9)

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Information about marking

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.



The CE marking means that this product meets the requirements of the regulation 2016/425

Mechanical hazard - EN 388:2016 + A1:2018



3 1 3 2 X

Levels of performance



Abrasion resistance	3	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

Read carefully the instructions for use provided with the product

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear...).

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available with product.